



Product Data Sheet

# Medical Shower Filter



[t-safe.com](https://t-safe.com)



# Medical Shower Filter



## Features

- Sterilising grade 0.2 µm rated hollow fiber membrane filter
- High capacity filter with up to 92 day life cycle
- Constant flow technology ensures optimal flow performance over life cycle
- Antimicrobial additive protection reduces risk of retrograde contamination
- Integral check valve prevents backflow contamination upstream
- Traceability with GS1 Datamatrix, enabling electronic tracking of filters

## Order Information

Item	Code
Medical Shower Filter	02-803121
Medical Shower Filter sterile	02-803125

## Technical Data

Max. operating pressure	5 bar
Max. operating temperature	60° C
Flow rate	8 L/min
Max. filter life cycle	92 days*
Connection	½ inch thread
Colour	White

### Microbial retention

Sterilising grade membrane filter, effective against all waterborne pathogens. Independently tested and validated in accordance with ASTM F838 against:

- *Legionella pneumophila*
- *Pseudomonas aeruginosa*
- *Brevundimonas diminuta*

### Microbial reduction

T-safe antimicrobial additive is proven to reduce surface bacteria contamination by 99.9%. Independently tested in accordance with ISO 22196.

### Approvals

ASTM F838-15A, ISO 22196, WRAS, KIWA, DVGW W270. Compliant with EU food and drinking water directives.

\* Dependent on local water quality and usage.

All information contained within this data sheet is based on the current knowledge and experience of T-safe. It is provided in good faith and is intended to serve only as a guideline for the selection and use of products. T-safe products should always be handled in accordance with the applicable Instruction for Use advice. The current data sheet is available at [www.t-safe.com](http://www.t-safe.com).